



HUD APPROVED MANUFACTURED HOME INSTALLATION WORKSHEET

MANUFACTURER: _____ YEAR: _____ LENGTH: _____ WIDTH: _____

WIND ZONE I _____ II _____ III _____

SOIL BEARING CAPACITY: _____ PSF (TESTED OR ASSUMED 1000 PSF)

A .. I BEAM PIER SPACING: _____ ' O.C. SIZE OF FOUNDATION PADS: _____ " X _____ "

B .. PERIMETER PIER SPACING: _____ ' O.C.(IF APPLICABLE)...SIZE OF PIER PADS: _____ " X _____ "

TYPICAL C/L PIER SPACING: _____ ' O.C.(IF APPLICABLE)...SIZE OF PIER PADS: _____ " X _____ "

D .. COLUMN/RIDGEBEAM SUPPORT FOUNDATION PADS:

SIZE OF PIER PADS	REQUIRED LOAD	SIZE OF PIER PADS	REQUIRED LOAD
D1 " X "	_____ LBS	D9 " X "	_____ LBS
D2 " X "	_____ LBS	D10 " X "	_____ LBS
D3 " X "	_____ LBS	D11 " X "	_____ LBS
D4 " X "	_____ LBS	D12 " X "	_____ LBS
D5 " X "	_____ LBS	D13 " X "	_____ LBS
D6 " X "	_____ LBS	D14 " X "	_____ LBS
D7 " X "	_____ LBS	D15 " X "	_____ LBS
D8 " X "	_____ LBS	D16 " X "	_____ LBS

E .. ANCHOR SPACING: _____ ' O.C. (MAXIMUM 5'4")

ANCHOR TYPE : ☐ TYPE I, 3150# WORKING LOAD or ☐ TYPE II, 4000# WORKING LOAD

TYPICAL DOUBLEWIDE

* REQUIRED LONGITUDINAL ANCHORING PROVIDED ☐ YES

* REQUIRED ANCHORS PROVIDED AT SHEARWALLS AND DESIGNATED LOCATIONS ☐ YES

D1 D2 D3 D4 D5 D6 D7 D8 D9 D10 D11 D12 D13 D14 D15 D16

* REQUIRED PERIMETER BLOCKING PROVIDED AT OPENINGS ☐ YES

| - "A" - |

"E"

"B"

NOTE: SUBMIT PROPER DOCUMENTATION FOR ALTERNATE SETUP/INSTALLATION MATERIALS UTILIZED.

TYPICAL SINGLEWIDE

* REQUIRED LONGITUDINAL ANCHORS PROVIDED ☐ YES

* REQUIRED PERIMETER BLOCKING PROVIDED AT OPENINGS ☐ YES

| - "A" - |

"B"

SPECIAL NOTE: THE MANUFACTURER'S BLOCKING DIAGRAM SHOWING SHEARWALL LOCATIONS & C/L LOADING ALONG WITH THE INSTALLATION MANUAL MUST BE SUBMITTED WITH THIS WORKSHEET FOR REVIEW PRIOR TO THE SETUP INSPECTION.

NAME of INSTALLER: _____

LICENSE NUMBER: _____

SIGNATURE: _____ DATE: _____

UNIT SPECIFIC SETUP DIAGRAMS ARE REQUIRED FOR TRIPLEWIDE OR TAG UNIT INSTALLATIONS.